



EXCAVATOR PLOW ATTACHMENT

Excavator attachment for trenchless installation of pipe or cable.

QUICK & EASY INSTALLATION

The Wolfe Excavator Plow allows for easy installation of fibre optics, flexible conduit, cable or pipe up to 120mm (4.75")* in diameter to a depth of 1500mm (60")* from grade (depending on ground conditions) without the need to dig a trench. The easy-to-attach plow can be installed on virtually any excavator.

*Maximum Diameter and Depth for Model EP-60



HEAVY DUTY VIBRATING UNIT

Reduces the amount of pull required from the excavator.



SIDE TILT

15 degree side tilt allows the shank to remain vertical while plowing on slopes.



SELF-CONTAINED HYDRAULIC VALVES

Only one auxiliary hydraulic circuit is required on the excavator, making the installation of the Plow Attachment quick and easy.



RUBBER ISOLATORS

Reduces the vibration that transfers through the excavator, minimizing the amount of vibration and noise in the operator's cab.

Wolfe Heavy Equipment is a powerful agricultural and commercial trenching manufacturer committed to providing superior engineering and expert service. UNEARTH THE POWER

WOLFE



OFFSET SWING

Offset swings left and right, making it possible to plow outside of the tracks. This allows the excavator to remain on the road while plowing along the side of the machine on the shoulder.

PENDANT CONTROL

The independent pendant control allows the operator to control the vibratory unit, the side tilt cylinders, and the offset swing cylinders. Virtually no wiring is required during the install onto the excavator.

MODEL	EP-36	EP-48	EP-60
Minimum Excavator (metric ton)	15	30	45
Maximum working depth (Inches / MM)	36 / 915	48 / 1220	60 / 1500
Maximum pipe outside diameter (Inches / MM)	2.0 / 50	2.75 / 70	4.75 / 120
Offset swing right and left (Inches / MM)	48 / 1200	48 / 1200	60 / 1500
Hydraulic Flow required (GPM / LPM)	26 / 100	36 / 136	48 / 182

